



| | |
|----------------|------------------|
| | |
| WL1680 | WL16120T |
| | |
| WL1680T | VL12P1696 |

General Description

WiPath produces a range of LED moving message displays with integrated intelligent paging receivers able to be deployed anywhere on a local area or wide area paging network.

These LED displays are used for a wide variety of messaging and information purposes including campus emergency mass alerting, information display and for specialized applications such as nursecall.

Applications

Emergency Mass Alert
Dispatch Centre Message Monitoring

Information Displays
Public Information

Nursecall Systems
Factory Alerts

Features

Available in 1, 2 and 4 lines (to order)
Indoor and outdoor models available
Very large capcode capacity
Relay control outputs capcode & message activated (option)

Date/Time display (option)
Paging receiver integrated -pocsag and Flex
Display and alerting functions controlled by message
Receivers available for most paging bands

Specifications

| | WL1680R | WL160T | WL16120R | VL12P1696 |
|----------------------|----------------|---------------|-----------------|------------------|
| Type | Indoor | Indoor | Indoor | Outdoor |
| Colour | Red | Tricolour | Red | Red |
| Resolution | 16x80 | 16x80 | 16x120 | 16x96 |
| No.Lines | 2 | 2 | 2 | 2 |
| No.Char/line | 16/8 | 16/8 | 24/12 | 20/12 |
| Pitch (mm) | 7.62 | 7.62 | 7.62 | 12 |
| Physical (mm) | 670x165x60 | 670x165x60 | 1000x165x60 | 1220x250x150 |
| (in.) | ~26x7x3 | ~26x7x3 | ~39x7x3 | ~48x10x6 |
| Power (VAC) | 100-240VAC | 100-240VAC | 100-240VAC | 100-240VAC |